







Shielded cables for industrial applications



Cable designation	Application	Connections	Length
Shielded standard round cable, twisted pairs and with metallized hoods			
 ST010 Connector cross section 0.14 mm ² twisted pairs, shielded	Connection to digital, analog I/O boards, relay output boards, counter boards and screw terminal board	37-pin SUB-D female connector 37-pin SUB-D male connector Wiring: 1:1	2 m
ST011	Connection to digital, analog I/O boards, relay output boards, counter boards and screw terminal board	37-pin SUB-D female connector 37-pin SUB-D male connector Wiring: 1:1	5 m
 ST010-S and ST011-S Connector cross section 0.25 mm ² for data line 0.752 mm ² (for external supply)	Connection to digital boards intended for higher currents CPCI-1500, APCI-1500, APCI-1564, APCI-2032, PA1500, PA 1508, PA 2000	same as ST010 and ST011 Wiring: 1:1	2 m, 5 m
ST021	Connection cable between CPCI-1500, APCI-1500, APCI-1516, PA1500, and relay output board PX 8500	37-pin SUB-D male connector 37-pin SUB-D female connector	2 m
 ST022	Connection cable between - 2 relay output boards PX 8500 - PX 8500 and PX 901-D or PX 9000	2 x 37-pin SUB-D male connector Wiring: 1:1	2 m
ST3122-A ST3122-D	Connection cable between APCI-3122/APCI-3504 and PX9200 analog outputs APCI-3122 and PX9200 digital inputs/outputs	2 x 26-pin SUB-D HD male connector 2 x 15-pin SUB-D HD male connector	2 m 2 m
ST3701	Connection cable between APCI-3701 and PX 3701-8	50-pin SUB-D male connector 50-pin SUB-D female connector	2 m
ST370-8	Connection cable between PA 370-8 and PX 371-8	50-pin SUB-D male connector 50-pin SUB-D female connector	2 m
ST370-16	Connection cable between - PA 370-16 and PX 371-16 - PA 2200 and PX 8000 - APCI/CPCI-1710 and PX 8000	50-pin SUB-D male connector 50-pin SUB-D female connector	2 m
ST8001	- PA 8000 or APCI-8001 and PX 8000		2 m

Other length on request

Cable designation	Application	Connections	Length
Connection cable, twisted pairs and with metallized hoods for the communication boards ADDICOM			
 ST074	Connection cable for 4-port serial interfaces (PA 7500, APCI-7500)	1 x 37-pin SUB-D female connector 4 x 25-pin SUB-D male connector	35 cm
ST075	Connection cable for 4-port serial interfaces (PA 7500, APCI-7500)	1 x 37-pin SUB-D female connector 4 x 9-pin SUB-D male connector	35 cm
 ST7809	Connection cable for 8-port serial interfaces (APCI-7800)	1 x 78-pin SUB-D male connector 8 x 9-pin SUB-D male connector	35 cm
 ST7825	Connection cable for 8-port serial interfaces (APCI-7800)	1 x 78-pin SUB-D male connector 8 x 25-pin SUB-D male connector	35 cm

Cable designation	Application	Connections	Length
Ribbon cable			
FB2200-1/FB1700	Ribbon cable for PA 2200-8-8 and PA 2200-16-8 or PA 1700-2	1 x 34-pin female connector 1 x 37-pin SUB-D male conn. with bracket	20 cm
FB3000	Ribbon cable for PA 3000, PA 3500, APCI-3120, APCI-3501, APCI-3001	1 x 16-pin female connector 1 x 37-pin SUB-D male conn. with bracket	25 cm
FB311	Ribbon cable for PA 311 oder PA 3100	1 x 26-pin female connector 1 x 37-pin SUB-D male conn. with bracket	35 cm