

Various combinations of Adaptors and I/O Application Modules can be connected to our Digital & Analog Multi-I/O Connectors.

Dimensions shown below exclude DIN-rail base.

DIGITAL Multi I/O Connectors

PC-43A1



- (1x) 16ch; (2x) 8ch Digital O/P Connectors
- (1x) 16ch; (2x) 8ch Digital I/P Connectors
- Dimensions: 72(W) x 99(L) x 19(H) mm

Used with any of the following boards:
PCI-62C; PCI-63C; PCI-773
 Cable used: **IDC40 or DB37M/F**

PC-43A2



- (1x) 16ch; (3x) 8ch Digital I/O Connectors
- Dimensions: 72(W) x 99(L) x 19(H) mm

Used with any of the following boards:
PC-36A/B/C; PCI-836A/C; PC-192/192A
 Cable used: **DB37M/F**

PCI-848A/C; PCI-896A/C; PCI-8192A/C
 Cable used: **IDC50**

PC-30DX; PC-30F/G Cable used: **Y-Cable2**

MicroDAQ Units Cable used: **DB25M/F**

PC-43A3



- (1x) 16ch; (3x) 8ch Digital I/P Connectors
- Counter Timer Screw Terminal
- Dimensions: 72(W) x 99(L) x 19(H) mm

Used with any of the following boards:
PCI-30G/GA; PCI-30G/GA-32; PCI-726/730
 Cable used: **IDC40 or DB37M/F**

PC-43A4



- 8 Independent Digital I/O Connectors
- Digital Control I/O Screw Terminal
- Dimensions: 72(W) x 99(L) x 19(H) mm

Used with any of the following boards:
PCI-703-16/16A
 Cable used: **Y-Cable1**

PCI-703-32/32A; PCI-703-64/64A
 Cable used: **Y-Cable3**

PCI-703S-8/8A/16/16A Cable used: **Y-Cable4**

PC-43A5



- (3x) 8ch; (1x) 16ch; (1x) 24ch Dig O/P Connectors
- (3x) 8ch; (1x) 16ch; (1x) 24ch Dig I/P Connectors
- Counter/Timer Screw Terminal
- Dimensions: 72(W) x 222.5(L) x 23(H) mm

Used with any of the following boards:
PCI-14B Cable used: **SCSI-C68M/M**

PC-14B Cable used: **IDC26 or DB25M/F**



Analog Multi I/O Connectors

PC-52A1



- (2x) 8ch; (4x) 4ch Analog I/P Connectors
- (1x) 2ch Analog O/P Connectors
- Analog EXT REF & I/P Sense Screw T.
- Dimensions: 72(W) x 110(L) x 19(H) mm

Used with any of the following boards:
PCI-703-16/16A
 Cable used: **Y-Cable1**

PC-52A2



- (2x) 8ch; (4x) 4ch Analog I/P Connectors
- (1x) 4ch Analog O/P Connectors
- Digital EXT TRIG & EXT CLK Screw Term.
- Dimensions: 72(W) x 110(L) x 19(H) mm

Used with any of the following boards:
PC-30DX; PC-30F/G Cable used: **Y-Cable2**

PCI-725; PCI-726; PCI-730; USB-30
 Cable used: **DB25M/F**

PC-52A3



- (4x) 8ch; (8x) 4ch Analog I/P Connectors
- (1x) 4ch Analog O/P Connectors
- (1x) 4ch Analog O/P Sense Screw T.
- Digital EXT TRIG & EXT CLK Screw T.
- Dimensions: 107.5(W) x 143.5(L) x 23(H) mm

Used with any of the following boards:
PCI-30G/GA/G-32/GA-32
 Cable used: **SCSI-C50M/M**

PC-52A4



- (8x) 8ch Analog I/P Connectors
- (1x) 2ch Analog O/P Connectors
- Analog EXT REF & I/P Sense Screw T.
- Dimensions: 107.5(W) x 178.5(L) x 13(H) mm

Used with any of the following boards:
PCI-703-32/32A; PCI-703-64/64A
 Cable used: **Y-Cable3**

PC-52A5



- (2x) 8ch; (4x) 4ch Analog I/P Connectors
- (1x) 2ch Analog O/P Connectors
- Dimensions: 107.5(W) x 125(L) x 23(H) mm

Used with any of the following boards:
PCI-703S-8/8A/16/16A Cable used: **Y-Cable4**

Should you require any assistance with selecting the correct accessories for your application, please do not hesitate to contact our sales personnel.

Alternatively consult the system diagrams on individual product pages to configure your system.